




Product Type: Compact intermediate relay

Product Name:RET-24DC-2C

Product Description: Compact industrial relay, 2transfer contact 24VDC/ 8A,Test button

Product Size



Parameters

⌘ SUPU ID	RET-24DC-2C
⌘ Protection Level	IP40
⌘ Ambient temperature (operation)	-25~+55°C

☞ Ambient temperature (storage)	-40~+70°C
☞ Mounting Type	optional
☞ Contact material	silver alloy
☞ Connection method	Push in connection
☞ Contact connection type	2C

Technical data

☞ IEC Rated Voltage	24DC
☞ Overvoltage category	II
☞ Degree of pollution	2
☞ Insulation Resistance	1000MΩ (500VDC)
☞ Dielectric withstand voltage	5000VAC 1min : Coils/ contacts 1000VAC 1min : BetweenContacts 3000VAC 6min : BetweenContacts
☞ Endurance	Mechanical 20 million cycles or more Electrical over 100,000 cycles
☞ Operating voltage	≤75% of rated voltage
☞ Release Voltage	≥10% of rated voltage
☞ Maximum permissible voltage	130% of rated voltage
☞ Nominal power consumption	About0.53W
☞ Response time	15ms or less
☞ Release time	20ms or less
☞ Protective circuit	None
☞ Status display	visual
☞ Maximum switching power	2200VA/240W
☞ Rated load capacity	AC277V/8A DC30V/8A

Commercial data

☞ Order No	RET-24DC-2C
☞ Packing unit	20
☞ Minimum order quantity	20
☞ Single piece weight	19g

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China
Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat