





Product Type: Optocoupler solid-state relay

Product Name: SCR-OP-24DC48DC-1A

Product Description: Optocoupler relay IN:24VDC
OUT:48VDC-1A

Product Size



Parameters

SUPU ID	SCR-OP-24DC48DC-1A
Contact plating	Tin
Product family	SCR Series
Certification in acc. with standard	EN61947-5-1:2017/AC:2020

☞ Mounting type	DIN 35mm rail mounting
☞ Assembly note	No spacing arrangement
☞ Mounting position	optional
☞ Connection type	NPN / PNP
☞ Wire Range	26-12/0.2-2.5mm ²
☞ Impulse withstand voltage	4KV
☞ 厚x宽x高 (mm)	6.2x90x72
☞ Plastic materials	PA66

Technical data

☞ IEC Rated Current	15~50mA
☞ Protective circuit	Anti-reverse protection, TVS surge protection
☞ Indicator light	Emerald (LED)
☞ Maximum switching frequency	500HZ
☞ Input polarity	Monopole
☞ Rated switching voltage	5~48VDC
☞ Rated switching current	100mA~1000mA
☞ Maximum switching voltage	48VDC
☞ Continuing current	1000mA
☞ Voltage dips	0.1V
☞ Load type	DC
☞ Load protection circuit	DC

Commercial data

☞ Order No	SCR-OP-24DC48DC-1A
☞ Packing unit	PCS
☞ Minimum order quantity	10
☞ Single piece weight	24.85

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat