




Product Type: Plug-in terminal-Plug

Product Name:MC-  
ROX7.5H04P-0002

Product Description: Pitch:7.5mm Rated  
Voltage : 630V Rated Current:20A Connection  
method : Spring cage connection  
colour : customizable

## Product Size



## Parameters

|                                                                                                         |                        |
|---------------------------------------------------------------------------------------------------------|------------------------|
|  SUPU ID               | MC-ROX7.5H04P-0002     |
|  Pitch                 | 7.5                    |
|  Number of connections | 4                      |
|  Connection method     | Spring cage connection |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn Plated/Au Plated Area         |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                         |
|-------------------------------------------------|-------------------------|
| ☞ IEC Rated Current                             | 20A                     |
| ☞ IEC Rated Voltage                             | 630V                    |
| ☞ Overvoltage category                          | III/III/ II             |
| ☞ Degree of pollution                           | 3 2 2                   |
| ☞ Rated impulse voltage                         | 6KV 6KV 6KV             |
| ☞ UL Rated Current                              | 14.5A - 5A              |
| ☞ UL Rated Voltage                              | 300V - 600V             |
| ☞ Conductor cross section rigid                 | 0.2-2.5mm <sup>2</sup>  |
| ☞ Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup>  |
| ☞ Conductor cross section flexible,with furrule | 0.25-1.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                       |
| ☞ Locking screw torque                          | -                       |
| ☞ Fixed Screw Specification                     | -                       |
| ☞ Stripping length                              | 8-9mm                   |
| ☞ Use group                                     | B/C/D                   |

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat