



Product Type: Plug-in terminal-Socket

Product Name:MC-PA3.5A08-I-0002

Product Description: Pitch: 3.5mm Rated
Voltage : 160V Rated Current: 8A
colour : customizable

Parameters

⌘ SUPU ID	MC-PA3.5A08-I-0002
⌘ Pitch	3.5
⌘ Number of connections	8
⌘ Connection method	-
⌘ Protection Level	IP20
⌘ Operating temperature range	-40~+105°C
⌘ Insulation material	PA66
⌘ Insulation material group	I
⌘ Contact material	Copper alloy
⌘ Contact plating	Sn,Plated
⌘ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

⌘ IEC Rated Current	160V
⌘ IEC Rated Voltage	8A

⌘ Overvoltage category	III III II
⌘ Degree of pollution	3 2 2
⌘ Rated impulse voltage	2.5KV 2.5KV 2.5KV
⌘ UL Rated Current	8A - 8A
⌘ UL Rated Voltage	300V - 300V
⌘ Conductor cross section rigid	-
⌘ Conductor cross section flexible	-
⌘ Conductor cross section flexible,with furrule	-
⌘ Locking screw Specification	-
⌘ Locking screw torque	-
⌘ Fixed Screw Specification	M2.5
⌘ Stripping length	-
⌘ Use group	B/C/D

Commercial data

⌘ Order No	MC-PA3.5A08-I-0002
------------	--------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-11-29 04:29

The right to modify data belongs to SUPU.