





Product Type: Barrier terminal

Product Name:TB-K-16.0VXXC-001

Product Description: pitch : 16.0mm, rated voltage UL600V, rated current UL75A, color: black, Rated cross section 22-4AWG

## Product Size



## Parameters

|                                                                                                          |                   |
|----------------------------------------------------------------------------------------------------------|-------------------|
|  SUPU ID               | TB-K-16.0V02C-001 |
|  Pitch                 | 16.0              |
|  Number of levels      | Single layer      |
|  Number of connections | XX                |

|                               |                  |
|-------------------------------|------------------|
| ☞ Connection method           | Screw connection |
| ☞ Protection Level            | IP20             |
| ☞ Operating temperature range | -30°C ~+120°C    |
| ☞ Insulation material         | PBT+GF           |
| ☞ Insulation material group   | III              |
| ☞ Contact material            | Copper alloy     |
| ☞ Contact plating             | Sn plated        |

## Commercial data

|            |                   |
|------------|-------------------|
| ☞ Order No | TB-K-16.0V02C-001 |
|------------|-------------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

