



Product Type: Barrier terminal

Product Name:TBD-14.5V09C-
40-101

Product Description: pitch : 14.5mm, rated voltage
IEC1000V, rated current IEC76A, color: black, Rated
cross section 20-8AWG

Product Size



Parameters

⌘ SUPU ID	TBD-14.5V09C-40-101
⌘ Pitch	14.5
⌘ Number of levels	single layer
⌘ Number of connections	9
⌘ Connection method	Screw connection
⌘ Protection Level	IP20
⌘ Operating temperature range	-30°C ~+120°C
⌘ Insulation material	PBT+GF

☞ Insulation material group	III
☞ Contact material	Copper alloy
☞ Contact plating	Sn plated

Technical data

☞ IEC Rated Current	76/76/76
☞ IEC Rated Voltage	630/1000/1000
☞ Overvoltage category	III/III/II
☞ Degree of pollution	3/2/2
☞ Rated impulse voltage	/
☞ Conductor cross section rigid	0.5-10
☞ Stripping length	13-14
☞ Tightening torque	22.1
☞ Connection capacity AWG	22-8
☞ UL Rated Current	50/50/10
☞ UL Rated Current	300/300/300

Commercial data

☞ Order No	TBD-14.5V09C-40-101
------------	---------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Ningbo SUPU Electronics Co., Ltd.

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-11-28 19:31

The right to modify data belongs to SUPU.