


A 3D perspective view of a green 10-pin D-sub connector. The connector has a long, rectangular body with a series of ten pins protruding from the bottom. The top of the connector features a D-shaped notch, characteristic of D-sub connectors. Two gold-colored screws are visible on the top surface, securing the cover. The overall design is compact and industrial.

## Product Size



## Parameters

|                       |                    |
|-----------------------|--------------------|
| SUPU ID               | MC-PA7.5H11-F-0002 |
| Pitch                 | 7.5                |
| Number of levels      | Single layer       |
| Number of connections | 11                 |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | -                                |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

Technical data

|                                                 |                   |
|-------------------------------------------------|-------------------|
| ☞ IEC Rated Current                             | 630V              |
| ☞ IEC Rated Voltage                             | 18A               |
| ☞ Overvoltage category                          | III III II        |
| ☞ Degree of pollution                           | 3 2 2             |
| ☞ Rated impulse voltage                         | 6.0KV 6.0KV 6.0KV |
| ☞ UL Rated Current                              | 15A - 10A         |
| ☞ UL Rated Voltage                              | 300V - 300V       |
| ☞ Conductor cross section rigid                 | -                 |
| ☞ Conductor cross section flexible              | -                 |
| ☞ Conductor cross section flexible,with furrule | -                 |
| ☞ Locking screw Specification                   | -                 |
| ☞ Locking screw torque                          | -                 |
| ☞ Fixed Screw Specification                     | -                 |
| ☞ 固定螺钉扭矩                                        | -                 |

|                       |       |
|-----------------------|-------|
| ☞ Stripping length    | -     |
| ☞ Use group           | B/C/D |
| ☞ Rated cross section | -     |

| Commercial data |                    |
|-----------------|--------------------|
| ☞ Order No      | MC-PA7.5H11-F-0002 |

Ningbo SUPU Electronics Co., Ltd.  
 Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
 Cixi City, Zhejiang Province, China  
 Zip code: 315303  
 Switchboard: +86 574-63288158  
 Fax: +86 574-63288170  
 E-mail:supucontact@supu.cn  
 Service Hotline: 400-626-6336



Wechat