



Product Type: Plug-in terminal-Socket

Product Name:MC-DPA5.0VXX-0002

Product Description: Pitch:5.0mm Rated
Voltage : 320V Rated Current:10A
colour : customizable

Parameters

⌘ SUPU ID	MC-DPA5.0VXX-0002
⌘ Pitch	5
⌘ Number of connections	XX
⌘ Connection method	-
⌘ Protection Level	IP20
⌘ Operating temperature range	-40~+105°C
⌘ Insulation material	PA66
⌘ Insulation material group	I
⌘ Contact material	Copper alloy
⌘ Contact plating	Sn,Plated
⌘ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

⌘ IEC Rated Current	10A
⌘ IEC Rated Voltage	320V

⌘ Overvoltage category	III III II
⌘ Degree of pollution	3 2 2
⌘ Rated impulse voltage	4.0KV 4.0KV 4.0KV
⌘ UL Rated Current	15A - 10A
⌘ UL Rated Voltage	300V - 300V
⌘ Conductor cross section rigid	-
⌘ Conductor cross section flexible	-
⌘ Conductor cross section flexible,with furrule	-
⌘ Locking screw Specification	-
⌘ Locking screw torque	-
⌘ Fixed Screw Specification	-
⌘ Stripping length	-
⌘ Use group	B/C/D

Commercial data

⌘ Order No	MC-DPA5.0VXX-0002
------------	-------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-01 07:04

The right to modify data belongs to SUPU.