



Product Type: Plug-in terminal-Socket

Product Name:MC-POX7.5HXX-0001

Product Description: Pitch: 7.5mm Rated

Voltage : 630V Rated Current: 15A

colour : customizable

Parameters

| | |
|-------------------------------|----------------------------------|
| ☞ SUPU ID | MC-POX7.5HXX-0001 |
| ☞ Pitch | 7.5 |
| ☞ Number of connections | XX |
| ☞ Connection method | - |
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PA66 |
| ☞ Insulation material group | I |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Gold Sn,Plated |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|---------------------|------|
| ☞ IEC Rated Current | 15A |
| ☞ IEC Rated Voltage | 630V |

| | |
|---|-------------------|
| ☞ Overvoltage category | III III II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 6.0KV 6.0KV 6.0KV |
| ☞ UL Rated Current | 15A 15A 10A |
| ☞ UL Rated Voltage | 300V 300V 300V |
| ☞ Conductor cross section rigid | - |
| ☞ Conductor cross section flexible | - |
| ☞ Conductor cross section flexible,with furrule | - |
| ☞ Locking screw Specification | - |
| ☞ Locking screw torque | - |
| ☞ Fixed Screw Specification | - |
| ☞ Stripping length | - |
| ☞ Use group | B/C/D |

Commercial data

| | |
|------------|-------------------|
| ☞ Order No | MC-POX7.5HXX-0001 |
|------------|-------------------|

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-02-25 23:07

The right to modify data belongs to SUPU.