



Product Type: Fixed terminal

Product Name:MC-TC5.08V31P-  
N-0001

Product Description: Pitch:5mm Rated

Voltage : 400V Rated Current:15A Connection

method : Push-in spring connection

colour : customizable

Product Size



Parameters

|                               |                      |
|-------------------------------|----------------------|
| ⌘ SUPU ID                     | MC-TC5.08V31P-N-0001 |
| ⌘ Pitch                       | 5.08                 |
| ⌘ Number of levels            | Single layer         |
| ⌘ Number of connections       | 31                   |
| ⌘ Connection method           | Push in connection   |
| ⌘ Protection Level            | IP20                 |
| ⌘ Operating temperature range | -40~+105°C           |
| ⌘ Insulation material         | PA66                 |

|                             |                                  |
|-----------------------------|----------------------------------|
| ☞ Insulation material group | I                                |
| ☞ Contact material          | Copper alloy                     |
| ☞ Contact plating           | Sn,Plated                        |
| ☞ Color                     | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 15A                    |
| ☞ IEC Rated Voltage                             | 400V                   |
| ☞ Overvoltage category                          | III/III/ II            |
| ☞ Degree of pollution                           | 3 2 2                  |
| ☞ Rated impulse voltage                         | 4.0KV 4.0KV 4.0KV      |
| ☞ UL Rated Current                              | 10A - 10A              |
| ☞ UL Rated Voltage                              | 300V - 300V            |
| ☞ Conductor cross section rigid                 | 0.2~1.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2~1.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2~1.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                      |
| ☞ Locking screw torque                          | -                      |
| ☞ Fixed Screw Specification                     | -                      |
| ☞ Stripping length                              | 10mm                   |

## Commercial data

|            |                      |
|------------|----------------------|
| ☞ Order No | MC-TC5.08V31P-N-0001 |
|------------|----------------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2025-11-28 22:39

The right to modify data belongs to SUPU.