




Product Type: Fixed terminal

Product Name:MC-TH10.16H06C-0001

Product Description: Pitch:10.16mm Rated Voltage : 1000V Rated Current:76A Connection method : Screw connection colour : customizable

Product Size



Parameters

| | |
|-----------------------|---------------------|
| SUPU ID | MC-TH10.16H06C-0001 |
| Pitch | 10.16 |
| Number of levels | Single layer |
| Number of connections | 6 |

| | |
|-------------------------------|----------------------------------|
| ☞ Connection method | Screw connection |
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PA66 |
| ☞ Insulation material group | I |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Sn,Plated |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|---|-----------------------|
| ☞ IEC Rated Current | 76A |
| ☞ IEC Rated Voltage | 1000V |
| ☞ Overvoltage category | III/III/ II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 8.0KV 8.0KV 8.0KV |
| ☞ UL Rated Current | 60A 60A - |
| ☞ UL Rated Voltage | 600V 600V - |
| ☞ Conductor cross section rigid | 0.5-16mm ² |
| ☞ Conductor cross section flexible | 0.5-16mm ² |
| ☞ Conductor cross section flexible,with ferrule | 0.5-16mm ² |
| ☞ Locking screw Specification | M4 |
| ☞ Locking screw torque | 1.2N.m |
| ☞ Fixed Screw Specification | - |
| ☞ Stripping length | 10-12mm |

☞ Order No

MC-TH10.16H06C-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat