


Product Type: Plug-in terminal-Socket

Product Name:MC-PH7.62V02-0001

Product Description: Pitch: 7.62mm Rated Voltage : 630V Rated Current: 32A colour : customizable

Product Size



Parameters

| | |
|-----------------------|-------------------|
| SUPU ID | MC-PH7.62V02-0001 |
| Pitch | 7.62 |
| Number of levels | Single layer |
| Number of connections | 2 |

| | |
|-------------------------------|----------------------------------|
| ☞ Connection method | - |
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PA66 |
| ☞ Insulation material group | I |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Sn,Plated |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|-------------------------|-------------------|
| ☞ IEC Rated Current | 630V |
| ☞ IEC Rated Voltage | 32A |
| ☞ Overvoltage category | III III II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 6.0KV 6.0KV 6.0KV |
| ☞ UL Rated Current | 20A 20A - |
| ☞ UL Rated Voltage | 300V 300V - |
| ☞ Use group | B/C/D |

Commercial data

| | |
|------------|-------------------|
| ☞ Order No | MC-PH7.62V02-0001 |
|------------|-------------------|

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-07 21:20

The right to modify data belongs to SUPU.