




Product Type: Plug-in terminal-Plug

Product Name:MC-RJ2.5H08P-0001

Product Description: Pitch:2.5mm Rated Voltage : 160V Rated Current:4A Connection method : Push-in spring connection colour : customizable

Product Size



Parameters

|                         |                   |
|-------------------------|-------------------|
| ⌘ SUPU ID               | MC-RJ2.5H08P-0001 |
| ⌘ Pitch                 | 2.5               |
| ⌘ Number of levels      | single layer      |
| ⌘ Number of connections | 8                 |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | Push in connection               |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 4A                     |
| ☞ IEC Rated Voltage                             | 160V                   |
| ☞ Overvoltage category                          | III/III/ II            |
| ☞ Degree of pollution                           | 3 2 2                  |
| ☞ Rated impulse voltage                         | 1.5KV 2.5KV2.5KV       |
| ☞ UL Rated Current                              | 4A - -                 |
| ☞ UL Rated Voltage                              | 125V - -               |
| ☞ Conductor cross section rigid                 | 0.2-0.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2-0.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-0.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                      |
| ☞ Locking screw torque                          | -                      |
| ☞ Fixed Screw Specification                     | -                      |
| ☞ 固定螺钉扭矩                                        | -                      |

|                       |          |
|-----------------------|----------|
| ⌘ Stripping length    | 7-8mm    |
| ⌘ Use group           | B/C/D    |
| ⌘ Rated cross section | 28~20AWG |

## Commercial data

|            |                   |
|------------|-------------------|
| ⌘ Order No | MC-RJ2.5H08P-0001 |
|------------|-------------------|

### Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat